TERYX KRX®4 1000 SE







LIME GREEN/METALLIC ONYX BLACK



SUNBEAM RED/METALLIC ONYX BLACK



POWER

4-stroke, DOHC, 8-valve parallel-twin, liquid cooled **Engine**

Displacement 999cc

Maximum Torque 76.7 lb-ft @ 7000 rpm

Bore x Stroke 92.0 x 75.1 mm

Compression Ratio 11.5:1

DEL with two 50mm throttle hodies **Fuel System**

TCBI with electronic advance Ignition

Starting System

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Selectable 2WD/4WD with locking front differential, shaft **Final Drive**

Engine Braking

Turning Radius 23.3 ft **Cargo Bed Dimensions** 14.6 x 33.1 x 9.1 in

(LxWxH)

Cargo Bed Load Capacity

Payload Capacity

Seating Capacity

Lighting

DETAILS

Curb Weight

N/A

351 lbs

1001 lbs

(2) LED headlights, (2) LED taillights, LED stoplight

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 LSC Piggyback Shocks, dual-rate coilover springs, fully adjustable preload, and 24-way adjustable

compression damping/18.6 in.

Rear Suspension / Wheel Travel

4-link trailing-arm rear suspension, FOX 2.5 LSC Piggyback Shocks, dual-rate coil-over springs, fully adjustable preload, and 24-way adjustable compression damping/21.1 in.

Front Tires MAXXIS Carnivore 31 x 10.00R15 8PR

Rear Tires MAXXIS Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.4 in (max), 13.6 in (std)

Fuel Capacity 10.6 gal

Towing Capacity

Ladder type, tubular steel

Overall Length 157.3 in

Overall Width 68.1 in

Overall Height 79.3 in

2163.1 lbs (2165.3 lbs CA)*

Wheelbase 125 8 in

Multi-function digital meter with bar-style tachometer (2 Instruments display options), digital speedometer, bar-style fuel gauge,

gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning

lamp, and CVT belt warning lamp.

Wheel Type Alloy wheels

Additional Features Roof, WARN® VRX 45 Winch

Color Choices Lime Green/Metallic Onyx Black, Sunbeam Red/Metallic Onyx

Warranty 6 months

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A.