MULE PRO-FXT™ 1000 PLATINUM RANCH EDITION







POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc **Maximum Torque** 61.5 lb-ft

Bore x Stroke 92.0 x 75.1mm

Compression Ratio

Fuel System DFI® with 38mm throttle body

Continuously Variable Transmission (CVT) with (L,H,N,R) Transmission

Selectable 2WD/4WD, shaft Dual mode rear differential with **Final Drive**

differential lock

Engine Braking

Alternator Output 90 amp

(max)

Fuel Capacity 7.9 gal **Turning Radius** 16.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity 1,616.3 lb / 1,263.5 lb CA Model

Seating Capacity

3-person (1 row), 6 person (2 row) 2,000 lb

Towing Capacity

Lighting

(4) LED headlights

DETAILS

Overall Length 140.2 in **Overall Width** 64.0 in **Overall Height** 80.9 in

Curb Weight 2,030.8 lb* / 2,033.0 lb* CA Model 92.3 in

Alloy

Wheelbase

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

indicators, seatbelt reminder lamps

Wheel Type

Additional Features

Warranty

Roof, Additional Front Cup Holders, WARN® VRX 45 Winch, Premium Seats, Premium Shoulder Pads, Self-Leveling Rear Suspension, Quad LED Headlights, Brush Guard, Headlight Guards, Rear Bumper, Anti-cinch Seat Belts, Rearview Mirror,

Additional Under Seat Storage Bin

Color Choices Metallic Stardust White

Kawasaki STRONG 3-Year Limited Warranty

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/11.0 in

Rear Suspension / Wheel Travel

Double wishbone/10.1 in

Front Tires 26 x 9.00-12, radial **Rear Tires**

26 x 11.00-12, radial

Steering

Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, Mechanical Disc

Front Brakes Rear Brakes

Dual Disc, 2 piston caliper Dual Disc, 1 piston caliper

Ground Clearance

12.6 in (max), 11.6 in (std)

Scan with camera to view videos, key features and more.

