VULCAN® 1700 VOYAGER® ABS









D	N	V	V	С	D
Г	U	V	V	C	π

Engine 4-stroke, 52-degree V-twin, liquid-cooled

Displacement 1.700cc/103.7 cu in

Bore x Stroke 102.0 x 104.0mm

Compression

Ratio

9.5:1

Maximum Torque 107.6 lb-ft @ 2750 rpm

DFI 42mm Throttle Bodies (2) **Fuel System**

Ignition TCBI w/ Electronic Advance

Transmission 6-speed with overdrive and positive neutral

finder

Final Drive Carbon fiber-reinforced belt

Electronic Rider Electronic cruise control, Kawasaki Advanced **Aids** Coactive-Braking Technology (K-ACT II) ABS

PERFORMANCE

Front Suspension / Wheel Travel

45mm Showa telescopic fork/5.5 in

Rear Suspension / Wheel Travel

Swingarm with twin air-assisted shocks, with 4-

way rebound damping/3.1 in

Front Tire 130/90-16 **Rear Tire** 170/70-16

Front Brakes Dual 300mm discs, dual four-piston calipers, K-

ACT II ABS

Rear Brakes Single 300mm disc, twin-piston caliper, K-ACT II

DETAILS

Frame Type Steel, double-cradle with box-section single-

tube backbone

30°/7.0 in Rake/Trail

Overall Length 100.8 in

Overall Width 39.2 in

61.0 in **Overall Height**

Ground 5.3 in

Clearance

Seat Height 28.7 in

Curb Weight 895.2 lb*

Fuel Capacity 5.3 gal

Wheelbase 65.6 in

Integrated audio system with SiriusXM ® and **Special Features**

intercom headset compatibility

PEARL ROBOTIC WHITE/PEARL NIGHTSHADE TEAL **Color Choices**

Warranty 36 Month Limited Warranty



