²⁰²² KLR[®]650 ABS





PEARL SAND KHAKI
 PEARL LAVA ORANGE



130/80-17

POWER

1 OHER		Front Brakes	Single 300mm disc with 2-piston calipers,
Engine	4-Stroke, single cylinder, DOHC		ABS
Displacement	652cc	Rear Brakes	Single 240mm disc with single-piston caliper, ABS
Bore x Stroke	100.0 x 83.0mm		
Compression Ratio	9.8:1	DETAILS	
Maximum	39.1 lbft. @ 4,500rpm	Frame Type	Tubular, Semi-Double Cradle
Torque		Rake/Trail	30.0°/4.8 in
Fuel System	DFI w/40mm Throttle Body	Overall Length	89.8 in
Ignition	CDI	Overall Width	38.2 in
Transmission	5-speed, return shift with wet multi-disc manual clutch	Overall Height	57.7/56.3 in (screen hi/lo)
Final Drive	Sealed Chain	Ground Clearance	8.3 in
PERFORMANCE		Seat Height	34.3 in
		Curb Weight	460.6 / 456.2 lb*

Rear Tire

Front 41mm telescopic fork/ 7.9 in **Fuel Capacity** Suspension / Wheel Travel Wheelbase Uni-Trak[®], single shock with adjustable Rear **Color Choices** rebound damping and adjustable spring Suspension / Wheel Travel preload / 8.0 in Warranty **Front Tire** 90/90-21

Warranty 12 Months
rerials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied

6.1 gal

60.6 in

Pearl Sand Khaki, Pearl Lava Orange

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.