²⁰²³ KLX®140R







90/100-14

POWER

IONLIN		Front Brakes	Single 220mm petal disc with a dual-
Engine	4-stroke single, SOHC, air-cooled		piston caliper
Displacement	144cc	Rear Brakes	Single 186mm petal disc with single- piston caliper
Bore x Stroke	58.0 x 54.4mm		
Compression Ratio	9.5:1	DETAILS	
Fuel System	20mm Keihin carburetor	Frame Type	High-tensile steel, box-section perimeter
Ignition	Digital DC-CDI	Rake/Trail	27°/3.3 in
Transmission	5-speed, return shift, with wet multi-disc	Overall Length	71.7 in
114115111551011	manual clutch	Overall Width	31.1 in
Final Drive	Chain	Overall Height	41.3 in
PERFORMANCE		Ground Clearance	9.3 in
Front	33mm telescopic fork/7.1 in	Seat Height	30.7 in
Suspension /			
Wheel Travel		Curb Weight	205.0 lb*
Wheel Travel Rear	Uni-Trak [®] linkage system and single shock	Curb Weight Fuel Capacity	205.0 lb* 1.5 gal
Wheel Travel	Uni-Trak® linkage system and single shock with 5-way preload adjustability/7.1 in	-	
Wheel Travel Rear Suspension /		Fuel Capacity	1.5 gal

Rear Tire





40

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.