²⁰²³ **KX**[™]112







POWER

Engine	2-stroke single with exhaust power valve (KIPS), liquid-cooled	
Displacement	112cc	
Bore x Stroke	52.5 x 51.6mm	
Compression Ratio	9.9:1 (Low speed)/8.6:1 (High speed)	
Fuel System	28mm Keihin carburetor	
Ignition	CDI with digital advance	
Transmission	6-speed, return shift, with wet multi-disc manual clutch	
Final Drive	Chain	

Rear Tire90/100-16Front BrakesSingle 220mm petal disc with dual-piston
caliperRear BrakesSingle 184mm petal disc with single-piston
caliper

DETAILS

	Frame Type	High-tensile steel perimeter design withsubframe member
	Rake/Trail	29°/4.3 in
i-disc	Overall Length	75.6 in
	Overall Width	30.1 in
	Overall Height	45.3 in
	Ground Clearance	13.0 in
fork 10.8 in	Seat Height	34.3 in
	Curb Weight	169.7 lb*
	Fuel Capacity	1.32 gal
amping in	Wheelbase	51.6 in
	Color Choices	Lime Green
	Warranty	Not Available

PERFORMANCE

Front Suspension / Wheel Travel	36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with 24-way compression and 21-way rebound damping plus adjustable spring preload/10.8 in
Front Tire	70/100-19

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.