

2023 KX™ 65

Kawasaki
Let the Good Times Roll®



 LIME GREEN



POWER

| | |
|-------------------|--|
| Engine | 2-stroke single, liquid-cooled |
| Displacement | 64cc |
| Bore x Stroke | 45.5 x 41.6mm |
| Compression Ratio | 8.4:1 |
| Fuel System | 24mm Mikuni carburetor |
| Ignition | CDI with digital advance |
| Transmission | 6-speed, return shift, with wet multi-disc manual clutch |
| Final Drive | Chain |

| | |
|--------------|--|
| Rear Tire | 80/100-12 |
| Front Brakes | Single 180mm disc with single-piston caliper |
| Rear Brakes | Single 180mm disc with single-piston caliper |

PERFORMANCE

| | |
|---------------------------------|--|
| Front Suspension / Wheel Travel | 33mm leading axle telescopic fork with 4-way rebound damping/8.3 in |
| Rear Suspension / Wheel Travel | Uni-Trak® single shock system with stepless 3-turns rebound damping and fully adjustable spring preload/9.4 in |
| Front Tire | 60/100-14 |

DETAILS

| | |
|------------------|---------------------------------------|
| Frame Type | High-tensile steel semi-double cradle |
| Rake/Trail | 27° / 2.4 in |
| Overall Length | 62.6 in |
| Overall Width | 29.9 in |
| Overall Height | 37.6 in |
| Ground Clearance | 12.0 in |
| Seat Height | 29.9 in |
| Curb Weight | 132.2 lb* |
| Fuel Capacity | 1.0 gal |
| Wheelbase | 44.1 in |
| Color Choices | Lime Green |
| Warranty | Not Available |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.