MULE PRO-FXT™ RANCH EDITION







POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3,500 rpm

2.83x2.62 in **Bore x Stroke**

Compression Ratio 9.5:1

DFI® with 34mm throttle body **Fuel System**

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Final Drive

with differential lock

Engine Braking Yes

Alternator Output

(max)

Selectable 2WD/4WD, shaft. Dual mode rear differential

75 amp

CAPABILITY

Wheel Travel

Front Suspension /

Rear Suspension /

Double wishbone/8.7 in

Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires

26x9.00-12, radial 26x11.00-12, radial

Rear Tires Steering

Park Brake Type

Electric Power Steering (EPS), Tilt steering

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Ground Clearance

Fuel Capacity

Turning Radius

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity

Seating Capacity

Towing Capacity

Lighting

10.0 in

7.9 gal

16.0 ft

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

person)

1,616.3 lb / 1,263.5 lb CA Model

3-person (1 row), 6 person (2 row)

2.000 lb

(2) Halogen headlights. (2) LED headlights

DETAILS

Overall Length 135.6 in

Overall Width 64.0 in

Overall Height 79.5 in

Curb Weight 1,971.3 lb*

Wheelbase 92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning

indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

Additional Features

Roof, WARN® VRX 45 Winch, Premium Seats, Front Bumper

Plates

Color Choices Metallic Titanium

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

