

2023

TERYX KRX® 4 1000 eS

Kawasaki

Let the Good Times Roll®




METALLIC FLAT RAW GRAYSTONE/
CANDY STEEL FURNACE ORANGE



POWER		DETAILS	
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Displacement	999cc	Cargo Bed Load Capacity	351 lbs
Maximum Torque	76.7 lb-ft @ 7000 rpm	Payload Capacity	1001 lbs
Bore x Stroke	92.0 x 75.1 mm	Seating Capacity	4
Compression Ratio	11.5:1	Towing Capacity	N/A
Fuel System	DFI with two 50mm throttle bodies	Lighting	(2) LED headlights, (2) LED taillights, LED stoplight
Ignition	TCBI with electronic advance	Instruments	
Starting System	Electric		
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	Frame	Ladder type, tubular steel
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	Overall Length	157.3 in
Engine Braking	Yes	Overall Width	68.1 in
CAPABILITY		Overall Height	76.2 in
		Curb Weight	2105.8 lbs (2108.0 lbs CA)*
Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in.	Wheelbase	125.8 in
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in.	Color Choices	
Front Tires	MAXXIS Carnivore 31 x 10.00R15 8PR		
Rear Tires	MAXXIS Carnivore 31 x 10.00R15 8PR	Warranty	6 months
Steering	Electric Power Steering (EPS) / rack-and-pinion	Multi-function digital meter with high-grade full-color TFT LCD screen that offers three selectable display modes (Digital, Analogue, Simple) and can auto adjust screen brightness to suit available light. Display functions include speedometer, tachometer, fuel gauge, gear indicator (L, H, N, R), driving mode (2WD/4WD/4WD+Diff Lock), power mode (Full/Low), suspension mode (Soft/Normal/Firm), clock, CVT temperature, digital tachometer, odometer, dual trip meters, total time, trip time, average speed, water temperature, battery voltage, Bluetooth indicator**, telephone call indicator, main indicator, economical riding indicator, maintenance reminder, neutral indicator, reverse indicator, headlight high-beam indicator, battery warning lamp, EPS warning lamp, CVT belt warning lamp, seatbelt warning lamp, parking indicator lamp, oil warning lamp, water temperature warning lamp, engine check lamp.	
Front Brakes	Dual hydraulic discs with two-piston calipers		
Rear Brakes	Dual hydraulic discs with single-piston calipers		
Ground Clearance	15.2 in (max), 14.2 in (std)		
Fuel Capacity	10.6 gal		
Turning Radius	23.3 ft		

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**When linked to a smartphone via Bluetooth, notification of call and messages received will be indicated on the instrument display. Note, compatibility is limited to iOS type smartphones.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.