## 2024 **VULCAN® 900 CLASSIC**





PEARL STORM GRAY/PEARL ROBOTIC WHITE



## **POWER**

Engine	4-stroke, 55-degree V-twin, liquid-cooled
Displacement	903cc/55.10 cu in
Bore x Stroke	88.0 x 74.2mm
Compression Ratio	9.5:1
Maximum Torque	58.2 lb-ft @ 3,500 rpm
Fuel System	DFI® with 34mm throttle bodies (2), with sub-throttle valves
Ignition	TCBI with Electronic Advance
Transmission	5-speed with positive neutral finder
Final Drive	Kevlar-reinforced belt

41mm Showa tele

Front Tire	130/90-16
Rear Tire	180/70-15
Front Brakes	Single 300mm hydraulic disc
Rear Brakes	Single 270mm hydraulic disc

## DETAILS

) rpm	Frame Type	Semi-double cradle, high-tensile steel
	Rake/Trail	32°/6.3 in
throttle bodies (2), with es	Overall Length	97.0 in
nic Advance	Overall Width	39.6 in
itive neutral finder	Overall Height	41.9 in
l belt	Ground Clearance	5.3 in
	Seat Height	26.8 in
	Curb Weight	619.6 lb*
escopic fork/5.9 in	Fuel Capacity	5.3 gal
	Wheelbase	64.8 in
arm, 7-way adjustable .1 in	Color Choices	Pearl Storm Gray/Pearl Robotic White
	Warranty	12 Month Limited Warranty

## PERFORMANCE

Front
Suspension /
Wheel Travel

Rear Suspension / Wheel Travel Uni-Trak® swinga spring preload/4.

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.