2024 KLX®110R L







POWER Engine 4-stroke single, SOHC, air-cooled Displacement 112cc **Bore x Stroke** 53.0 x 50.6mm Compression 9.5:1 Ratio **Fuel System** 18mm Keihin carburetor and screw type throttle limiter on grip housing Ignition DC-CDI Transmission 4-speed, return shift, wet multi-disc **Overall Height** 39.0 in manual clutch 10.4 in Ground **Final Drive** Chain Clearance

PERFORMANCE

Front Suspension / Wheel Travel	30mm hydraulic telescopic fork/5.5 in
Rear Suspension / Wheel Travel	Swingarm with single hydraulic shock/5.2 in
Front Tire	2.50 x 14

Rear Tire	3.00 x 12	
Front Brakes	90mm mechanical drum, cable actuated	
Rear Brakes	110mm mechanical drum, rod actuated	
DETAILS		
Frame Type	Backbone frame, high-tensile steel	
Rake/Trail	24.2°/1.9 in	
Overall Length	61.4 in	
Overall Width	25.6 in	

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.

Seat Height

Curb Weight

Fuel Capacity

Color Choices

Wheelbase

Warranty

28.7 in

1.0 gal

42.3 in

6 Months

Lime Green, Battle Gray

167.5 lb*

Scan with camera to view videos, key features and more.

