²⁰²⁴ KLX®140R







POWER Engine 4-stroke single, SOHC, air-cooled Displacement 144cc **Bore x Stroke** 58.0 x 54.4mm Compression 9.5:1 Ratio 20mm Keihin carburetor **Fuel System** Ignition **Digital DC-CDI** Transmission 5-speed, return shift, with wet m manual clutch **Final Drive** Chain

PERFORMANCE

Front Suspension / Wheel Travel	33mm telescopic fork/7.1 in	9
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with 5-way preload adjustability/7.1 in	F
Front Tire	70/100-17	0

Rear Tire	90/100-14
Front Brakes	Single 220mm petal disc with a dual- piston caliper
Rear Brakes	Single 186mm petal disc with single- piston caliper

DETAILS

nulti-disc	Frame Type	High-tensile steel, box-section perimeter
	Rake/Trail	27°/3.3 in
	Overall Length	71.7 in
	Overall Width	31.1 in
	Overall Height	41.3 in
	Ground Clearance	9.3 in
ingle shock //7.1 in	Seat Height	30.7 in
	Curb Weight	205.0 lb*
	Fuel Capacity	1.5 gal
	Wheelbase	49.6 in
	Color Choices	Lime Green, Battle Gray
	Warranty	6 Month Limited Warranty





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.