## 2024 **KLX®140R F**







4.10 x 18

## **POWER**

			Front Brakes	Single 220mm petal disc with a dual-
	Engine	4-stroke single, SOHC, air-cooled		piston caliper
	Displacement	144cc	Rear Brakes	Single 186mm petal disc with single- piston caliper
	Bore x Stroke	58.0 x 54.4mm		
	Compression Ratio	9.5:1	DETAILS	
	Fuel System	20mm Keihin carburetor	Frame Type	High-tensile steel, box-section perimeter
	Ignition	Digital DC-CDI	Rake/Trail	27°/4.6 in
	Transmission	5-speed, return shift, with wet multi-disc manual clutch	<b>Overall Length</b>	78.9 in
			Overall Width	31.1 in
	Final Drive	Chain	Overall Height	44.7 in
	PERFORMANCE		Ground Clearance	12.4 in
	Front Suspension / Wheel Travel	33mm telescopic fork/7.5 in	Seat Height	33.9 in
			Curb Weight	218.2 lb*
	Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with piggyback reservoir, 20-way rebound damping and threaded preload adjustability/7.9 in	Fuel Capacity	1.5 gal
			Wheelbase	52.4 in
			Color Choices	Lime Green, Battle Gray

**Rear Tire** 

**Front Tire** 



Ē

2.75 x 21

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.

Warranty

6 Month Limited Warranty