MULE PRO-FXR™ 1000









POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (L,H,N,R)

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 90 amp

(max)

Ground Clearance 13.2 in (max), 12.2 in (std)

Fuel Capacity 7.9 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

999 lb / 600.0 lb CA Model

37.6 x 53.3 x 11.0 in

Cargo Bed Load Capacity

1,616.3 lb / 1,263.5 lb CA Model

Payload Capacity Seating Capacity

Towing Capacity

2,000 lb

Lighting

(2) Halogen headlights. (2) LED headlights

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/11.0 in

Rear Suspension / **Wheel Travel**

Double wishbone/10.1 in

Front Tires 27 x 9.00-12, radial

27 x 11.00-12, radial Electric Power Steering (EPS), Tilt steering Steering

Park Brake Type

Rear Tires

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

DETAILS

Overall Length 122.0 in

Overall Width 64.0 in

Overall Height 77.2 in

Curb Weight 1,735.3 lb* / 1,737.5 lb* CA Model

Wheelbase 79.7 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Additional Features Rear Bumper, Contoured Two-Tone Bench Seat

Color Choices Metallic Sierra Blue

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

