NINJA® ZX™-4R ABS









POWER

Engine 4-stroke, In-Line Four, OHC, 16-valve, liquid-

cooled

Displacement 399cc

Bore x Stroke 57.0 x 39.1mm

Compression

Ratio

12.3:1

Fuel System DFI® with 34mm throttle valves (4)

Ignition Digital

Transmission 6-speed, manual, return shift

Final Drive Chain

Electronic Rider

Aids

Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Power

Modes, Anti-lock Brake System (ABS)

PERFORMANCE

Front
Suspension /
Wheel Travel

37mm inverted fork with SFF-BP internals/4.7 in

| |

Rear Suspension / Wheel Travel Horizontal Back-link, Showa shock w/adjustable spring preload/4.4 in

Front Tire 110/70-17

Rear Tire 160/60-17

Front Brakes Dual 290mm discs, ABS

Rear Brakes Single 220mm disc, ABS

DETAILS

Frame Type Trellis, high-tensile steel

Rake/Trail 23.5°/3.8 in

Overall Length 78.3 in

Overall Width 30.1 in

Overall Height 43.7 in

Ground 5.3 in Clearance

Seat Height 31.5 in

Curb Weight 414.5 lb*

Fuel Capacity 4.0 gal

Wheelbase 54.3 in

Special 4.3" Full-Color TFT Instrumentation,

Features Smartphone Connectivity via RIDEOLOGY THE

APP

Color Choices Metallic Spark Black

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.

