TERYX® KRX4™ 1000 SE









POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 76.7 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio

Fuel System DFI® with two 50mm throttle bodies

TCBI with Flectronic Advance Ignition

Starting System Electric

Automatic CVT with centrifugal clutch (H,L,N,R) **Transmission**

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking

Turning Radius 23.3 ft

14.6 x 33.1 x 9.1 in Cargo Bed Dimensions (LxWxH)

Cargo Bed Load 351 lb

Capacity

Payload Capacity 1,001 lb

Seating Capacity

Towing Capacity N/A

Lighting (2) LED headlights, (2) LED taillights, LED stoplight

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 LSC Piggyback Shocks, dual-rate coil-over springs, fully adjustable preload, and 24-way

adjustable compression damping/18.6 in

Rear Suspension / **Wheel Travel**

4-link trailing-arm rear suspension, FOX 2.5 LSC Piggyback Shocks, dual-rate coil-over springs, fully adjustable preload, and 24-way adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR Maxxis® Carnivore 31 x 10.00R15 8PR **Rear Tires**

Steering Electric Power Steering (EPS) / rack-and-pinion

Dual hydraulic discs with two-piston calipers **Front Brakes**

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.4 in (max), 13.6 in (std)

Fuel Capacity 10.6 gal

DETAILS

Ladder type, tubular steel Frame

Overall Length 157.3 in **Overall Width** 68.1 in **Overall Height** 79.3 in

Curb Weight 2,163.1 lb* / 2,165.3 lb* CA Model

Wheelbase 125.8 in

Instruments

Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp.

Additional Features

Roof, WARN® VRX 45 Winch

Color Choices

Pearl Matte Sage Green/Metallic Carbon Gray

Warranty

6 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.