#### 2024

# TERYX® S LE







METALLIC MATTE TWILIGHT BLUE/SUPER BLACK



ICE GRAY/SUPER BLACK



## **POWER**

**Engine** 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

Maximum Torque 47.0 lb-ft @ 5,500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio

Fuel System DFI® with two 36mm Mikuni throttle bodies

Ignition TCBI with Electronic Advance

10.7:1

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

Fuel Capacity

Turning Radius 17.7 ft

Cargo Bed

**Dimensions (LxWxH)** 

27.6 x 43.3 x 10.4 in

Cargo Bed Load

Capacity

600 lb

7.9 gal

**Payload Capacity** 

1,100 lb

Seating Capacity

Towing Capacity 1,300 lb

Lighting (4) LED headlights, (2) incandescent taillights,

incandescent stoplight

# **CAPABILITY**

Front Suspension / Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.7 in

Rear Suspension / Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.0 in

Maxxis® 27 x 11-14

Front Tires Maxxis® 27 x 9-14

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc

Ground Clearance 12.2 in (max) / 11.2 in (std)

### **DETAILS**

Frame Steel Tube Double-X Reinforcement

Overall Length 118.1 in

Overall Width 62.2 in

Overall Height 78.5 in

**Curb Weight** 1,596.4 lb\* / 1,598.6 lb\* CA Model

Wheelbase 88.2 in

Instruments Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter and

parking-brake indicator, R/N/P/4WD, water temp and

low-oil-pressure indicators

Wheel Type Alloy

Additional Features Roof

Color Choices Metallic Matte Twilight Blue-/Super Black, Ice Gray/Super

Black

Warranty Kawasaki Strong 3-Year Limited Warranty



**Rear Tires** 

