2024 **VULCAN®** S







120/70x18

POWER

I ONER			160/60x17
ement	4-stroke, 2-cylinder, DOHC, liquid-cooled 649cc	Front Brakes	Single 300mm disc with twin-piston caliper, (and ABS)
Stroke	83.0 x 60.0mm	Rear Brakes	Single 250mm disc with single-piston caliper (and ABS)
		DETAILS	
Torque		Frame Type	High-tensile steel diamond frame
stem	DFI® with 38mm throttle bodies (2), with sub- throttle valves	Rake/Trail	31°/4.7 in
ı	TCBI with Electronic Advance	Overall Length	90.9 in
ission	6-speed with positive neutral finder		34.6 in 43.3 in
rive	Sealed chain	-	5.1 in
nic Rider	Economical Riding Indicator, Anti-lock Brake System (ABS)	Clearance	
PERFORMANCE		Seat Height	27.8 in
	ement Stroke Ssion m stem ission ive nic Rider	4-stroke, 2-cylinder, DOHC, liquid-cooledement649ccStroke83.0 x 60.0mmassion10.8:1m46.3 lb-ft @ 6,600 rpmstemDFI® with 38mm throttle bodies (2), with sub- throttle valvesstemDFI® with 28mm throttle bodies (2), with sub- throttle valvesission6-speed with positive neutral finderiveSealed chainice RiderEconomical Riding Indicator, Anti-lock Brake System (ABS)	Kear Tire 4-stroke, 2-cylinder, DOHC, liquid-cooled Front Brakes 649cc 83.0 x 60.0mm stroke 83.0 x 60.0mm 10.8:1 m 46.3 lb-ft @ 6,600 rpm stem DFI® with 38mm throttle bodies (2), with sub- throttle valves TCBI with Electronic Advance Noverall Length Overall Width Overall Width Overall Height stem Sealed chain fic Rider Economical Riding Indicator, Anti-lock Brake System (ABS)

Front Tire

PERFURMANCE

Front	41mm telescopic fork/5.1 in	Fuel Capacity	3
Suspension / Wheel Travel		Wheelbase	e
Rear Suspension /	Lay-down offset rear shock with linkage and adjustable preload/3.2 in	Color Choices	F
Wheel Travel		Warranty	1

	Overall Length	90.9 in			
	Overall Width	34.6 in			
	Overall Height	43.3 in			
	Ground Clearance	5.1 in			
	Seat Height	27.8 in			
	Curb Weight	498.3 lb* (ABS), 491.7 lb* (non-ABS)			
	Fuel Capacity	3.7 gal			
	Wheelbase	62.0 in			
	Color Choices	Pearl Sand Khaki/Ebony, Metallic Flat Spark Black			
	Warranty	12 Month Limited Warranty			
is to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).					

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.