## <sup>2024</sup> Z e-1 ABS





METALLIC BRIGHT SILVER/MATTE LIME GREEN/EBONY



## **POWER**

Scan with camera

to view videos,

key features

and more.

| Motor Type                         | Air-cooled, interior permanent magnet synchronous motor                    |
|------------------------------------|--|
| Power Modes                        | 2 Modes (ROAD/ECO) plus e-boost  |
| Max Speed by Mode                  | ROAD = 53 mph (63 mph with e-boost), ECO = 40 mph<br>(45 mph with e-boost) |
| Rated Power                        | 5.0 kW / 2,800 min-1   |
| Maximum Power                      | 9.0 kW / 2,600-4,000 min-1   |
| Maximum Torque                     | 29.7 lb-ft @ 500 rpm   |
| Battery Type                       | Lithium-ion battery pack (x2)  |
| Battery Voltage/<br>Capacity       | 50.4 V 30 Ah (x2)  |
| Battery Range                      | 41 mi (approximate in ROAD Mode w/o e-boost)                               |
| Battery Charge<br>Time (0 to 100%) | 3.7 hours (x2)   |
| Transmission Type                  | Single reduction gear  |
| Shifter Mechanism                  | Push button  |
| Primary Reduction<br>Ratio         | 3.211 (61/19)  |
| Final Reduction<br>Ratio           | 3.867 (58/15)  |
| Final Drive Type                   | Chain  |
| Electronic Rider<br>Aids           | WALK Mode (with Reverse), Anti-lock Brake System<br>(ABS)                  |
|                                    |  |

## PERFORMANCE

| Front Suspension/<br>Wheel Travel | 41mm telescopic front fork/4.7 in   |
|-----------------------------------|---|
| Rear Suspension/<br>Wheel Travel  | Bottom-Link Uni-Trak® with single gas-charged shock, adjustable spring preload/5.2 in |
| Front Tire                        | 100/80-17M/C 52S  |
| Rear Tire                         | 130/70-17M/C 62S  |
| Front Brakes                      | Single 290mm disc with dual-piston caliper  |
| Rear Brakes                       | Single 220mm disc with dual-piston caliper  |

## DETAILS

| Frame Type       | Trellis, high-tensile steel  |
|------------------|--|
| Rake & Trail     | 24.4° / 3.7 in   |
| Overall Length   | 78.0 in  |
| Overall Width    | 28.7 in  |
| Overall Height   | 40.7 in  |
| Ground Clearance | 6.7 in   |
| Seat Height      | 30.9 in  |
| Curb Weight      | 297.7 lb*  |
| Wheelbase        | 53.9 in  |
| Special Features | ERGO-FIT®, TFT Instrumentation with Smartphone<br>Connectivity via RIDEOLOGY THE APP, Battery<br>Temperature-Charge-Remaining Range Indicators |
| Color Choices    | Metallic Bright Silver/Matte Lime Green/Ebony  |
| Warranty         | 24 Month Limited Warranty  |
|                  |  |

\*Curb weight includes all necessary materials and batteries to operate correctly, and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.