

2025

Z900 ABS



-
- METALLIC SPARK BLACK/METALLIC CARBON GRAY/EBONY
-
-
- GALAXY SILVER/METALLIC SPARK BLACK/PHANTOM BLUE



POWER		Rear Tire	180/55-17
Engine	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled	Front Brakes	Dual 300mm semi-floating discs with radial-mount 4-piston calipers and ABS
Displacement	948cc	Rear Brakes	Single 250mm disc with single-piston caliper and ABS
Bore x Stroke	73.4 x 56.0mm	DETAILS	
Compression Ratio	11.8:1	Frame Type	Trellis, high tensile steel
Maximum Horsepower	123.0 hp ¹ @ 9,500 rpm	Rake/Trail	24.7° / 4.3 in
Maximum Torque	73.1 lb-ft @ 7,700 rpm	Overall Length	81.3 in
Fuel System	DFI® with 36mm throttle bodies	Overall Width	32.7 in
Ignition	TCBI with Electronic Advance	Overall Height	43.3 in
Transmission	6-speed, return shift	Ground Clearance	5.7 in
Final Drive	Sealed chain	Seat Height	31.9 in
Electronic Rider Aids	Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness	Dry Weight	423.4 lb** / 425.6 lb** 50-State Model
PERFORMANCE		Curb Weight	467.5 lb* / 469.7 lb* 50-State Model
Front Suspension / Wheel Travel	41mm inverted telescopic fork with rebound damping and spring preload adjustability/4.7 in	Fuel Capacity	4.5 gal
Rear Suspension / Wheel Travel	Horizontal back-link, gas-charged rear shock with rebound damping and spring preload adjustability/5.5 in	Wheelbase	57.1 in
Front Tire	120/70-17	Special Features	5" All-digital TFT color instrumentation, All-LED lighting, ERGO-FIT®, Smartphone Connectivity with Voice Command and Turn-by-Turn Navigation via RIDELOGY THE APP MOTORCYCLE
		Color Choices	Metallic Spark Black/Metallic Carbon Gray/Ebony, Galaxy Silver/Metallic Spark Black/Phantom Blue
		Warranty	12 Month Limited Warranty

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.