Z900 SE ABS









POWER

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

123.0 hp1 @ 9,500 rpm

Displacement 948cc

Bore x Stroke 73.4 x 56.0mm

Compression Ratio

Maximum

Horsepower

Maximum Torque 73.1 lb-ft @ 7,700 rpm

DFI® with 36mm throttle bodies **Fuel System**

11.8:1

Ignition TCBI with Electronic Advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider Aids Economical Riding Indicator, Electronic Cruise Control,

Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-

Enhanced Chassis Orientation Awareness

PERFORMANCE

Front Suspension / **Wheel Travel**

41mm inverted telescopic fork with compression and rebound damping and spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link, Öhlins S46 gas-charged rear shock with rebound damping and spring preload

adjustability/5.5 in

Front Tire 120/70-17

Rear Tire 180/55-17

Front Brakes Dual 300mm semi-floating discs with radial-mount 4-

piston Brembo M4.32 monobloc calipers and ABS

Rear Brakes Single 250mm disc with single-piston caliper and ABS

DETAILS

Frame Type Trellis, high tensile steel

24.7° / 4.3 in Rake/Trail

Overall Length 81.3 in

Overall Width 32.7 in

Overall Height 44.7 in

Ground Clearance 5.7 in

Seat Height 31.9 in

Estimated Dry Weight

425.6 lb** / 427.8 lb** 50-State Model

Curb Weight 469.7 lb* / 471.9 lb* 50-State Model

Fuel Capacity 4.5 gal

Wheelbase 57.1 in

Special Features 5" All-digital TFT color instrumentation, All-LED lighting,

USB Type-C outlet, ERGO-FIT®, Smartphone Connectivity with Voice Command and Turn-by-Turn Navigation via

RIDEOLOGY THE APP MOTORCYCLE

Color Choices Metallic Matte Graphite Gray/Ebony/Metallic Graphite

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©?2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.