ELEKTRODE® 20









P	N	V	V	F	R

Air-cooled, brushless, in-wheel **Motor Type Power Modes** 3 modes (High / Mid / Low)

Max Speed by Mode -H/M/L

Lithium-ion (in-frame)

24 mph / 24 mph / 13 mph

Battery Voltage/ Capacity

Battery Type

50.4 V 10.2 Ah (514.1 Wh)

Battery Charge Time

4 hours (approx)*

Drive System

Direct hub motor, chainless

Battery Rated Output

750 W

Battery Running Time

Low: 180 minutes / High: 60 minutes

Maximum Battery Charge Cycles

500 (after which 80% of original charge capacity)

PERFORMANCE

Frame Type **Aluminum**

Front Suspension/ **Wheel Travel**

28mm telescopic fork / 50mm

Rear Suspension/ Wheel Travel

28mm telescopic fork / 50mm

Front Tire 20 x 2.125 **Rear Tire** 20 x 2.125

Front Brakes 160mm mechanical disc 160mm mechanical disc **Rear Brakes**

Handlebar Clamp Size

Steering Stem Size

22.2mm

28.6mm

Seat Post Size

27.2mm

DETAILS

Rake & Trail 25 deg / 2.95 in (75mm)

Overall Length 59.3 in (1,505mm)

Overall Width 26.3 in (668mm)

36.6 in (929mm) **Overall Height**

Ground Clearance 7.1 in (181mm)

Seat Height 21.6-27.3 in (550-693mm)

38.93 in (989mm) Wheelbase **Curb Weight** 46.1 lb (20.9 kg)

Color Choices Lime Green, Black

Appropriate Rider's

Rider Weight (max) 132 lb (60 kg)

Yes (rotating pedal, foldable) **Footrest**

110-V AC (Home)

Front of bike

Charging power

source

Charging connector Number plate STD, MX-Style

WARRANTY

Frame and Fork TBA Non-Electrical TBA Components

Electric System Components

TBA

Normal Wear and Tear Items

TBA

Scan with camera to view videos, key features and more.

