## KLX®300R









## **POWER**

Engine 4-stroke, single-cylinder, DOHC, liquid-cooled

Displacement 292cc

Bore x Stroke 78.0 x 61.2mm

Compression Ratio

**Fuel System** 

----

DFI® with 34mm Keihin throttle body

Ignition TCBI with electronic advance

11.0:1

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

Rear Tire 4.6 x 18

Front Brakes Single 270mm petal disc with a dual-

piston caliper

**Rear Brakes** Single 240mm petal disc with single-

piston caliper

## **PERFORMANCE**

Front
Suspension /
Wheel Travel
43mm inverted telescopic fork with
adjustable compression damping/11.2 in

Rear Suspension / Wheel Travel Uni-Trak® gas charged shock with piggyback reservoir with adjustable compression, rebound damping and

spring preload/11.2 in

Front Tire 3.0 x 21

## **DETAILS**

Frame Type Semi-double cradle

Rake/Trail 26.9°/4.3 in

Overall Length 86.6 in

Overall Width 32.5 in

Overall Height 49.0 in

Ground 11.8 in Clearance

Seat Height 35.4 in

**Curb Weight** 282.2 lb\* / 286.7 lb\* 50-State Model

Fuel Capacity 2.1 gal

Wheelbase 56.5 in

**Color Choices** Lime Green, Battle Gray

**Warranty** 6 Month Limited Warranty



