## NINJA® 500 SE ABS







METALLIC FLAT SPARK BLACK/METALLIC SPARK BLACK/ METALLIC MOONDUST GRAY



PASSION RED/METALLIC FLAT SPARK BLACK/ METALLIC MATTE DARK GRAY



## **POWER**

Engine 4-stroke, Parallel Twin, DOHC, liquid-cooled

Displacement 451cc

70.0 x 58.6mm

Bore x Stroke
Compression

Ratio

11.3:1

Maximum Torque 31.7 lb-ft @ 7,500 rpm

Fuel System DFI® with dual 32mm throttle bodies

**Ignition** TCBI with Digital Advance

Transmission 6-speed

Final Drive Sealed chain

Scatca chair

Electronic Rider

Economical Riding Indicator, Anti-lock Brake

System (ABS)

## **PERFORMANCE**

Front Suspension / 41mm hydraulic telescopic fork/4.7 in / Wheel Travel

Rear Suspension /

Horizontal back-link with adjustable spring

Wheel Travel preload/5.1 in

Front Tire

110/70-17

**Rear Tire** 

150/60-17

Front Brakes Single 310mm se

Single 310mm semi-floating disc with 2-piston

calipers and ABS

**Rear Brakes** Single 220mm disc with single-piston caliper and

ABS

## **DETAILS**

Frame Type Trellis, high-tensile steel

Rake/Trail 24.7°/3.6 in

Overall Length 78.5 in

Overall Width 28.7 in

Overall Height 46.5 in

**Ground Clearance** 5.7 in

Seat Height 30.9 in

**Estimated Dry** 

Weight

348.4 lb\*\* / 350.6 lb\*\* 50-State Model

**Curb Weight** 379.3 lb\* / 381.5 lb\* 50-State Model

Fuel Capacity 3.7 gal

Wheelbase 54.1 in

Special Features ERGO-FIT®, Full-color TFT Instrumentation with

Smartphone Connectivity via RIDEOLOGY THE APP, Kawasaki's Intelligent Proximity Activation Start

System (KIPASS), USB-C outlet

Color Choices

Lime Green/Ebony/Pearl Blizzard White

**Warranty** 12 Month Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.