
NINJA® ZX™-10R KRT EDITION









POWER

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression Ratio 13.0:1

196.0 hp1 @ 11,500 rpm

Maximum

Horsepower

Maximum Torque

Fuel System

Ignition

Transmission

Final Drive

Electronic Rider Aids

TCBI with electronic advance

6-speed

Sealed chain

83.9 lb-ft @ 11,300 rpm

DFI®, 47mm throttle bodies

Öhlins Electronic Steering Damper, Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS)

(upshift & downshift), Kawasaki Corner Management

Function (KCMF)

PERFORMANCE

Front Suspension / **Wheel Travel**

43mm inverted Showa Balance Free Fork (BFF), adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link with Showa Balance Free Rear Cushion (BFRC) lite shock, stepless, dual-range (low-/ high-speed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in

Front Tire 120/70 ZR17

Rear Tire 190/55 ZR17

Front Brakes Brembo dual semi-floating 330mm discs with dual radial mounted monobloc 4-piston calipers, Kawasaki

Intelligent anti-lock Brake System (KIBS) (ABS only)

Single 220mm disc with aluminum single-piston caliper, **Rear Brakes**

Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS

only)

DETAILS

Frame Type Aluminum perimeter

Rake/Trail 25.0°/4.1 in

Overall Length 82.1 in **Overall Width** 29.5 in

Overall Height 46.7 in

Ground Clearance 5.3 in

Seat Height 32.9 in

456.4 lb* (ABS), 452.0 lb* (non-ABS) **Curb Weight**

Fuel Capacity 4.5 gal Wheelbase 57.1 in

Special Features 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Lime Green/Ebony/Pearl Blizzard White

12 Month Limited Warranty Warranty



