## 2025 RIDGE<sup>®</sup> XR CREW LIMITED HVAC





METALLIC BLUISH GRAY

12.9 gal

19.0 ft

2,500 lb

161.1 in

64.0 in

82.3 in

122.2 in

All-LED lighting

34.6 x 49.0 x 12.8 in

1,000/600 lb CA Model

1,290/1,076 lb CA Model

5-person (2 row), bench seats

Ladder type, tubular steel

2,513.7/2,515.9 lb\*\* CA Model

2,624.0/2,626.2 lb\* CA Model



## POWER

Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled		
Displacement	999cc		
Maximum Horsepower	116.0 hp1 @ 8,500 rpm		
Maximum Torque	73.8 lb-ft @ 8,000 rpm		
Bore x Stroke	73.4 x 59.0mm		
Compression Ratio	10.6:1		
Fuel System	EFI		
Ignition	TCBI with Digital Advance		
Starting System	Electric		
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)		
Final Drive	Selectable 4WD with locking front/rear differential, shaft		
Engine Braking	Yes		
Alternator Output (max)	85 amp		
Electronic Rider Aids	Power Modes, Economical Riding Indicator		

## CAPABILITY

Front Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil
Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in		change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery,
Front Tires	SUNF 30 x 10-14		EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
Rear Tires	SUNF 30 x 10-14	Additional Features	8" Garmin Tread®, WARN® VRX 45-S Powersport Winch, Full Cab
Wheel Type	14" Aluminum		with HVAC, Adjustable driver/passenger seats, ERGO-FIT®, Full- color TFT Instrumentation with Smartphone Connectivity via
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)		RIDEOLOGY THE APP Powersports, USB ports, KQR™ system compatible
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers	Color Choices	Metallic Bluish Gray
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers	Warranty	Kawasaki STRONG 3-Year Limited Warranty
Ground Clearance	13.4/14.6 in (max preload); 13.4 in CA Model		

**Fuel Capacity** 

**Turning Radius** 

(LxWxH) Cargo Bed Load

Capacity Payload Capacity

Lighting

Frame Overall Length

**Seating Capacity** 

**Towing Capacity** 

DETAILS

**Overall Width** 

**Overall Height** 

**Curb Weight** 

Wheelbase

**Estimated Dry Weight** 

**Cargo Bed Dimensions** 





10

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.