
VERSYS® 1100 SE ABS









120/70-17

180/55-17

System (KIBS)

POWER

Engine 4-stroke, in-line 4-cylinder, DOHC, liquid-cooled

Displacement 1,099cc

Bore x Stroke 77.0 x 59.0mm

Compression Ratio 11.8:1

Maximum 133.0 hp¹ @ 9,000 rpm Horsepower

Maximum Torque 82.5 lb-ft @ 7,600 rpm

Fuel System DFI® with 38mm throttle bodies (4)

Ignition TCBI with Electronic Advance

Transmission 6-speed, return shift with wet multi-disc manual Assist &

Slipper Clutch

Final Drive Chain

Electronic Rider Aids Economical Riding Indicator, Electronic Cruise Control,

Kawasaki TRaction Control (KTRC), Kawasaki Electronic Control Suspension (KECS), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis

Orientation Awareness

DETAILS

Front Tire

Rear Tire

Front Brakes

Rear Brakes

Frame Type Twin-tube, aluminum

Rake/Trail 27.0°/4.0 in

Overall Length 89.4 in

Overall Width 37.4 in

Overall Height 60.2 in (windshield Hi) / 59.8 in (windshield Lo)

Ground Clearance 5.9 in
Seat Height 33.1 in

Estimated Dry 520.4 l

Weight

520.4 lb** (+20 lb w/ saddlebags)

Curb Weight 571.1 lb* (+20 lb w/ saddlebags)

Fuel Capacity 5.5 gal

Wheelbase 59.8 in

Special Features Full-color TFT Instrumentation, All-LED lighting including

Cornering Lights, USB Type-C outlet, Adjustable windshield, Grip heaters and hand guards, ERGO-FIT®, Highly Durable Paint, Smartphone Connectivity with Voice

Command via RIDEOLOGY THE APP MOTORCYCLE

Dual 310mm petal discs with radial-mount 4-piston monobloc calipers, Kawasaki Intelligent anti-lock Brake

Single 260mm petal disc with single-piston caliper,

Kawasaki Intelligent anti-lock Brake System (KIBS)

Color Choices Metallic Graphite Gray/Metallic Diablo Black

Warranty 24 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel 43mm inverted Showa fork with KECS-controlled rebound and compression damping, manual spring preload adjustability and top-out springs/5.9 in

Rear Suspension / Wheel Travel Horizontal back-link, Showa BFRC Lite gas-charged shock with piggyback reservoir, KECS-controlled compression and rebound damping electronically-adjustable spring preload/5.9 in

Scan with camera to view videos, key features and more.

