## NEW 2026 BRUTE FORCE® 750 SE EPS





METALLIC GOLD SPARKLE DEEP GREEN



## POWER

Engine	4-stroke, V-twin, SOHC, liquid-cooled
Displacement	749cc
Bore x Stroke	85.0 x 66.0mm
Compression Ratio	9.3:1
Maximum Horsepower	50.0 hp1 @ 6,750 rpm
Maximum Torque	42.8 lb-ft @ 4,750 rpm
Fuel System	DFI® with two 34mm throttle bodies
Ignition	Digital DC-CDI
Transmission	Automatic Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD with variable control front differential lock, shaft

Double wishbon

Double wishbon

AT 25 x 8-12

AT 25 x 10-12

Dual hydraulic 1 Sealed, oil-bath

8.7 in/9.6 in (ma

Electric

5.0 gal

## SteeringRack-and-pinion w/ Electric Power Steering (EPS)Turning Radius10.5 ftTowing Capacity1,250 lbTotal Rack Capacity264.5 lbRack Capacity, Front/<br/>Rear88.0/176.0 lbLightingAll-LED lighting

## DETAILS

34mm throttle bodies			
	Frame Type	Double-cradle, high-tensile tubular steel	
tinuously Variable Transmission (CVT) with	Tread Width	37.0/35.6 in	
	Overall Length	88.4 in	
0/4WD with variable control front differential lock,	Overall Width	46.7 in	
	Overall Height	47.8 in	
	Seat Height	35.2 in	
ne, adjustable spring preload/6.9 in	Estimated Dry Weight	723.2 lb**	
	Curb Weight	769.5 lb*	
ne, adjustable spring preload/7.4 in	Wheelbase	50.6 in	
176mm discs with 2-piston calipers	Instruments	Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h), battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, EPS, and battery voltage)	
hed, multi-disc with independent park brake	Special Features	WARN® VRX 25-S Powersport Winch, Front brush guard, Hand	
ax preload)		guards, Full-color TFT Instrumentation w/ Smartphone Connectivity via RIDEOLOGY THE APP POWERSPORTS, KQR™ system	
	Color Choices	Metallic Gold Sparkle Deep Green	
	Warranty	12 Month Limited Warranty	



CAPABILITY

Front Suspension /

Rear Suspension / Wheel Travel Front Tires

Wheel Travel

**Rear Tires** 

**Front Brakes** 

Rear Brakes Ground Clearance

**Starting System** 

**Fuel Capacity** 



\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2025 Kawasaki Ators Corp., U.S.A. Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).