BRUTE FORCE® 750 SE EPS CAMO









Rack-and-pinion w/ Electric Power Steering (EPS)

Double-cradle, high-tensile tubular steel

POWER

Engine 4-stroke, V-twin, SOHC, liquid-cooled

749cc **Displacement**

Bore x Stroke 85.0 x 66.0mm

Compression Ratio 9.3:1

Maximum Horsepower 50.0 hp1 @ 6,750 rpm

DFI® with two 34mm throttle bodies **Fuel System**

Digital DC-CDI Ignition

Transmission Automatic Continuously Variable Transmission (CVT) with

42.7 lb-ft @ 4,750 rpm

(H,L,N,R)

Final Drive Selectable 2WD/4WD with variable control front differential

lock, shaft

CAPABILITY

Maximum Torque

Front Suspension / Wheel Travel

Rear Suspension / Double wishbone, adjustable spring preload/7.4 in Wheel Travel

Front Tires AT 25 x 8-12 **Rear Tires** AT 25 x 10-12

Dual hydraulic 176mm discs with 2-piston calipers **Front Brakes**

Rear Brakes

Ground Clearance 9.0 in/9.7 in (max preload)

Starting System Electric 5.0 gal **Fuel Capacity**

Double wishbone, adjustable spring preload/6.9 in

Sealed, oil-bathed, multi-disc with independent park brake

Turning Radius 10.5 ft

Towing Capacity 1,250 lb **Total Rack Capacity** 264.5 lb Rack Capacity, Front/ 88.0/176.0 lb

Rear

All-LED lighting Lighting

DETAILS

Frame Type

Special Features

Steering

Fread Width	37.0/35.6 in
Overall Length	86.0 in
Overall Width	46.1 in
Overall Height	47.6 in
Seat Height	35.2 in
Estimated Dry Weight	685.8 lb**
Curb Weight	732.1 lb*
Wheelbase	50.6 in
nstruments	Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h), battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, EPS, and battery voltage

d warning lights S, and battery voltage) Full-color TFT Instrumentation w/ Smartphone Connectivity via

RIDEOLOGY THE APP POWERSPORTS, KQR™ system

Color Choices TRUETIMBER® STRATA

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or

Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.

go to www.atvsafety.org. © 2025 Kawasaki Motors Corp., U.S.A.