

ALL-NEW 2026

KLX[®]230 DF ABS



 MEDIUM CLOUDY GRAY



POWER

Engine	4-stroke single, SOHC, air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.4:1
Maximum Torque	13.3 lb-ft @ 6,400 rpm
Fuel System	DFI [®] with 32mm throttle body
Ignition	TCBI with Electronic Advance
Transmission	6-speed
Final Drive	Sealed chain

PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/7.9 in
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with adjustable spring preload/8.8 in
Front Tire	2.75 x 21
Rear Tire	4.10 x 18

Front Brakes	Single 265mm petal disc with a dual-piston caliper
Rear Brakes	Single 220mm petal disc with single-piston caliper

DETAILS

Frame Type	High-tensile steel, perimeter
Rake/Trail	24.6° / 3.8 in
Overall Length	81.9 in
Overall Width	36.2 in
Overall Height	45.3 in
Ground Clearance	9.4 in
Seat Height	33.3 in
Dry Weight	284.4 lb**
Curb Weight	302.1 lb*
Fuel Capacity	2.0 gal
Wheelbase	53.7 in
Special Features	ERGO-FIT [®] , Aluminum skid plate, Engine guards, Hand guards, All-digital Instrumentation with Smartphone Connectivity
Color Choices	Medium Cloudy Gray

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.