ALL-NEW 2026

KLX[®]230 SHERPA S ABS







n		1	м	
r	U	M	V	K

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

Maximum Torque 14.0 lb-ft @ 6,400 rpm

Fuel System DFI® with 32mm throttle body

Ignition TCBI with Electronic Advance

Transmission 6-speed

Final Drive Sealed chain

PERFORMANCE

Front 37mm telescopic fork/6.2 in

Suspension / Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/6.6 in

Suspension / Wheel Travel

Front Tire

Rear

2.75 x 21

Rear Tire 4.10 x 18

Front Brakes

Single 265mm petal disc with a dual-piston

caliper

Rear Brakes

Single 220mm petal disc with single-piston

caliper

DETAILS

Frame Type High-tensile steel, perimeter

Rake/Trail 24.4°/3.8 in

Overall Length 81.1 in

Overall Width 36.2 in

Overall Height 44.3 in

Ground 8.5 in

Clearance

Seat Height

Dry Weight 282.2 lb** / 284.3 lb** 50-State Model

Curb Weight 297.7 lb* / 299.9 lb* 50-State Model

32.5 in

Fuel Capacity 2.0 gal

Wheelbase 53.3 in

Special Features | ERGO-FIT®, Even lower seat height, Aluminum

skid plate, Hand guards, All-digital
Instrumentation with Smartphone

Connectivity

Color Choices Whitish Beige



