2026

KLX[®]300









POWER

4-stroke, single-cylinder, DOHC, liquid-cooled **Engine**

Displacement 292cc

Bore x Stroke

78.0 x 61.2mm

Compression

Ratio

11.1:1

Maximum Horsepower 25.0 hp1 @ 8,000 rpm

Maximum Torque

17.7 lb-ft @ 7,000 rpm

Fuel System

DFI® with 34mm Keihin throttle body

Ignition

Transmission

6-speed, return shift with wet multi-disc manual

clutch Chain

Final Drive

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted telescopic fork with adjustable compression damping/10.0 in

Rear Suspension / Wheel Travel

Uni-Trak® gas charged shock with piggyback reservoir with adjustable compression, rebound

damping and spring preload/9.1 in

Front Tire

3.0 x 21

Rear Tire 4.6 x 18

Front Brakes Single 250mm petal disc with a dual-piston

caliper

Rear Brakes Single 240mm petal disc with single-piston

caliper

DETAILS

Frame Type Tubular, semi-double cradle

26.7° / 4.2 in Rake/Trail

Overall Length 85.6 in

Overall Width 32.3 in

Overall Height 46.7 in

Ground Clearance 10.8 in

Seat Height 35.2 in

Estimated Dry

Weight

282.2 lb**

Curb Weight 302.1 lb*

Fuel Capacity 2.0 gal

Wheelbase 56.7 in

Color Choices Lime Green, Bright White, Cypher Camo Beige/

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.

