

2026

MULE PRO-FXT™ 1000 PLATINUM RANCH EDITION

Kawasaki
Let the Good Times Roll®



 METALLIC DEEP RED



POWER

Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled, gas
Displacement	999cc
Maximum Horsepower	70.0 hp ¹ @ 6,500 rpm
Maximum Torque	61.5 lb-ft @ 4,500 rpm
Bore x Stroke	92.0 x 75.1mm
Compression Ratio	10.1:1
Fuel System	DFI® with 38mm throttle body
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	Yes
Alternator Output (max)	90 amp

Ground Clearance	12.6 in (max), 11.6 in (std)
Fuel Capacity	7.9 gal
Turning Radius	16.0 ft
Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)
Cargo Bed Load Capacity	999 lb (3-person)/350 lb (6-person)/348 lb CA Model
Payload Capacity	1,466.3/1,162.0 lb CA Model
Seating Capacity	3-person (1 row), 6 person (2 row)
Towing Capacity	2,000 lb
Lighting	(4) LED headlights

CAPABILITY

Front Suspension / Wheel Travel	Double wishbone/11.0 in
Rear Suspension / Wheel Travel	Double wishbone/10.1 in
Front Tires	26 x 9-12, radial
Rear Tires	26 x 11-12, radial
Steering	Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering
Park Brake Type	Independent, mechanical disc
Front Brakes	Dual disc, 2-piston caliper
Rear Brakes	Dual disc, 1-piston caliper

DETAILS

Overall Length	140.2 in
Overall Width	64.0 in
Overall Height	80.9 in
Estimated Dry Weight	1,988.9/1,991.1 lb** CA Model
Curb Weight	2,072.7/2,074.9 lb* CA Model
Wheelbase	92.3 in
Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Additional Features	Roof, Additional Front Cup Holders, WARN® VRX 45 Winch, Premium Seats, Premium Shoulder Pads, Self-Leveling Rear Suspension, Quad LED Headlights, Brush Guard, Headlight Guards, Rear Bumper, Anti-cinch Seat Belts, Rearview Mirror, Additional Under Seat Storage Bin
Color Choices	Metallic Deep Red

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.