MULE SX™ 4x4 XC







POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401c

Maximum 13.3 hp¹ @ 4,000 rpm

Horsepower

- -

Bore x Stroke 82.0 x 76.0mm

Compression Ratio 8.6:1

Maximum Torque

Fuel System Fuel Injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

21.4 lb-ft @ 2,400 rpm

Engine Braking No

Alternator Output 22.9 amp

(max)

Front Brakes Drum

Rear Brakes Drum

Ground Clearance 8.1 in

Fuel Capacity 4.2 gal

Turning Radius 4.2 ga

Cargo Bed 35.6 x 40.9 x 9.6 in

Cargo Bed Load 399 lb

Dimensions (LxWxH)

Capacity

Payload Capacity 900 lb
Seating Capacity 2

Towing Capacity 1,100 lb***

Lighting (2) Halogen headlights, tail/brake lights

CAPABILITY

Front Suspension / Wheel Travel MacPherson Strut/3.1 in

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

Front Tires

Rear Tires 26 x 9-12

26 x 9-12

Steering

Rack-and-pinion

Park Brake Type

Independent, mechanical drum

DETAILS

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 73.4 in

Estimated Dry Weight 1,043.0 lb**

Curb Weight 1,082.7 lb*

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake light

Color Choices Metallic Sierra Blue

Scan with camera to view videos, key features



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

***Requires optional hitch.

'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.