## **MULE SX™ 4x4 XC**









## **POWER**

**Engine** 4-stroke, single-cylinder, OHV, air-cooled

Displacement

Maximum 13.3 hp1 @ 4,000 rpm Horsepower

21.4 lb-ft @ 2,400 rpm **Maximum Torque** 

Bore x Stroke 82.0 x 76.0mm

**Compression Ratio** 8.6:1

**Fuel System Fuel Injection** 

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential **Final Drive** 

with differential lock

**Engine Braking** 

**Alternator Output** 22.9 amp

(max)

Front Brakes Drum **Rear Brakes** Drum

**Ground Clearance** 8.1 in

**Fuel Capacity** 4.2 gal

**Turning Radius** 11.8 ft

Cargo Bed **Dimensions (LxWxH)** 

**Cargo Bed Load** 

Capacity

**Payload Capacity** 900 lb

**Seating Capacity** 

**Towing Capacity** 1,100 lb\*\*\*

Lighting (2) Halogen headlights, tail/brake lights

1,082.7 lb\*

35.6 x 40.9 x 9.6 in

399 lb

## CAPABILITY

Front Suspension / Wheel Travel

MacPherson Strut/3.1 in

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

**Front Tires** 

26 x 9-12

**Rear Tires** 26 x 9-12

Rack-and-pinion Steering

**Park Brake Type** Independent, mechanical drum

## **DETAILS**

**Curb Weight** 

**Overall Length** 106.7 in **Overall Width** 52.6 in

**Overall Height** 73.4 in

**Estimated Dry Weight** 1,043.0 lb\*\*

Wheelbase

70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake light

**Color Choices** Metallic Sierra Blue

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*\*Requires optional hitch.

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit paraguay.kawasaki-la.com for full product details.