## **Z900 ABS**







METALLIC SPARK BLACK/METALLIC CARBON GRAY/EBONY



GALAXY SILVER/METALLIC SPARK BLACK/PHANTOM BLUE



## **POTENCIA**

Motor 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Cilindrada 948cc

Diámetro por carrera 73.4 x 56.0mm

Relación de

compresión

Potencia máxima

Par motor máximo

Sistema de

combustible

Encendido

Transmisión

Transmisión final

Asistencia

electrónica para el piloto

11.8:1

123.0 hp1 @ 9,500 rpm

73.1 lb-ft @ 7,700 rpm

DFI® with 36mm throttle bodies

TCBI with Flectronic Advance

6-speed, return shift

Sealed chain

Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-

**Enhanced Chassis Orientation Awareness** 

## RENDIMIENTO

Suspensión delantera/recorrido del neumático

spring preload adjustability/4.7 in

Suspensión trasera/ recorrido del neumático

Neumático delantero

41mm inverted telescopic fork with rebound damping and

Horizontal back-link, gas-charged rear shock with rebound damping and spring preload adjustability/5.5 in

120/70-17

Neumático trasero 180/55-17

Frenos delanteros Dual 300mm semi-floating discs with radial-mount 4-piston

calipers and ABS

Single 250mm disc with single-piston caliper and ABS Frenos traseros

Trellis, high tensile steel

## DETALLES

Tipo de chasis

Tipo de chasis	Trettis, filgir terisite steet
Ángulo de dirección/ Avance	24.7° / 4.3 in
Largo total	81.3 in
Ancho total	32.7 in
Altura del asiento	43.3 in
Distancia al suelo	5.7 in
Altura del asiento	31.9 in
Peso seco estimado	423.4 lb** / 425.6 lb** 50-State Model
Peso en orden de marcha	467.5 lb* / 469.7 lb* 50-State Model
Depósito de combustible	4.5 gal
Distancia entre ejes	57.1 in
Características especiales	5" All-digital TFT color instrumentation, All-LED lighting, ERGO-FIT®, Smartphone Connectivity with available Voice Command and Turn-by-Turn Navigation via RIDEOLOGY THE APP MOTORCYCLE***

Metallic Spark Black/Metallic Carbon Gray/Ebony, Galaxy

Silver/Metallic Spark Black/Phantom Blue

12 Month Limited Warranty

Escanear con cámara para ver videos, características clave y más.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Colores disponibles** 

Garantía

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*\*RIDEOLOGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©?2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visite paraguay.kawasaki-la.com para obtener detalles completos del producto.