NUEVA 2027

TERYX® H2 LIMITED eS

Kawasaki
Let the Good Times Roll®

METALLIC MATTE GRAPHENESTEEL GRAY/LIME GREEN

GRIS ICE/FLAT EBONY

POTENCIA

Motor	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled
Cilindrada	999cc
Potencia máxima	250.0 hp[1] @ 9,000 rpm
Par máximo	146.3 lb-ft @ 8,800 rpm
Diámetro x Carrera	73.4 x 59.0mm
Relación de compresión	7.8:1
Sistema de combustible	DFI® with (4) 40mm throttle bodies with dual injection; Kawasaki Supercharger
Ignition	TCBI with electronic advance
Arranque	Electric
Transmisión	Continuously Variable Transmission (CVT) with (H,L,N,R)
Transmisión final	Selectable 2WD/4WD with locking front differential, shaft
Freno motor	Yes
Electronic Rider Aids	Economical Riding Indicator, Power Modes, Kawasaki TRaction Control (KTRC), IMU-Enhanced Chassis Orientation Awareness, FOX Live Valve Sway Bar Disconnect

CAPACIDAD

Suspensión delantera/ recorrido del neumático	Double wishbone, FOX 3.0 Live Valve Internal Bypass shocks with piggyback reservoir, KECS+-controlled compression damping, and manually adjustable spring preload/23.2 in
Suspensión trasera/ recorrido del neumático	4-link trailing-arm rear suspension, FOX 3.0 Live Valve Internal Bypass shocks with piggyback reservoir, KECS+-controlled compression damping, and manually adjustable spring preload/24.0 in
Neumáticos delanteros	Maxxis® Carnivore Plus 33 x 10.00R16
Neumáticos traseros	Maxxis® Carnivore Plus 33 x 10.00R16
Wheel Type	16-in aluminum bead-lock wheels
Dirección	Electric Power Steering (EPS) / rack-and-pinion
Freno delantero	270mm dual hydraulic discs with 3-piston calipers
Freno trasero	270mm dual hydraulic discs with 2-piston calipers
Altura libre al suelo	16.9 in (max) / 16.1 in (std)
Capacidad de combustible	14.8 gal
Radio de giro	21.3 ft
Dimensiones del compartimento de carga (LxAxA)	14.6 x 33.1 x 9.1 in
Capacidad de carga del compartimento de carga	300 lb
Capacidad de carga útil	732 lb
Capacidad de asientos	2 bucket seats with 4-point seatbelts
Luces	All-LED lighting

DETALLES

Cuadro	Ladder type, tubular steel
Longitud total	134.1 in
Anchura total	74.0 in
Altura total	73.4 in / 78.3 in (with antenna)
Peso seco estimado	2,165.3 lb* / 2,167.5 lb** CA Model
Peso en orden de marcha	2,297.6 lb* / 2,299.8 lb* CA Model
Distancia entre ejes	101.0 in
Instrumentación	Digital speedometer, tachometer, fuel gauge, gear indicator (L, H, N, R), Driving Mode (2WD/4WD/4WD+Diff Lock), Power Mode (Full/Mid/Low), Suspension Mode (Soft/Normal/Firm), Camera Mode, Economical Riding Indicator, connected indicator, clock, odometer, dual trip meters, total time, trip time, average speed, engine temperature, intake air temperature, battery voltage, boost pressure, CTV temperature, seatbelt warning lamp, maintenance reminder, oil warning lamp, engine check lamp, engine temperature warning lamp, neutral indicator, reverse indicator, headlight high-beam indicator, parking indicator lamp, battery warning lamp, EPS warning lamp, and CVT belt warning lamp
Características adicionales	10-in Garmin Tread® with (2) 6.5-in speakers and (2) 2-in tweeters, 7-in Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP POWERSPORTS, Plastic roof, Skid plates w/ drain holes, ERGO-FIT®, 1 DC outlet, 2 USB ports, 4 cup holders, Additional storage
Opciones de color	Metallic Matte Graphenesteel Gray/Lime Green, Ice Gray/Flat Ebony

Escanear con cámara para ver videos, características clave y más.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
[1]This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The TERYX® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki TERYX side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visite paraguay.kawasaki-la.com para obtener detalles completos del producto.